

2013/10/16

595RS-R

SER	SIZE	PR	LI/SS	OVERALL Diameter		Section Width		Standard Rim in	Approved Rim Width	Tread Width		Tread Depth		Weight KG	MAX. PSI cold	Max. Load		UTQG	Side Wall	Tyres	RR	Wet Grip (dBS)	E_Sound	
				mm	in	mm	in			mm	in	in32	mm			KGS	LBS							
30	285/30ZR18		97W XL	626	24.6	290	11.4	10.0	9.5-10.5	259	10.2	8	6.2	13.3	50	730	1609	140AA A	BSW	C1	F	E	72	1
35	245/35ZR18		88W	627	24.7	248	9.8	8.5	8.0- 9.0	224	8.8	8	6.5	11.7	44	560	1234	140AA A	BSW	C1	F	E	72	3
	255/35ZR18		90W	634	25.0	260	10.2	9.0	8.5- 9.5	236	9.3	8	6.5	12.5	44	600	1323	140AA A	BSW	C1	F	E	72	2
	265/35ZR18		93W	643	25.3	271	10.7	9.5	9.0-10.0	246	9.7	8	6.5	12.8	44	650	1433	140AA A	BSW	C1	F	E	72	2
40	215/40ZR17		83W	603	23.7	222	8.7	7.5	7.0- 8.5	190	7.5	9	7.5	10.1	44	467	1074	140AA A	BSW	C1	F	E	72	3
	235/40ZR17		90W	619	24.4	238	9.4	8.5	8.0- 9.5	216	8.5	8	6.5	11.3	44	600	1323	140AA A	BSW	C1	F	E	72	3
	255/40ZR17		94W	634	25.0	260	10.2	9.0	8.5-10.0	232	9.1	8	6.5	12.4	44	670	1477	140AA A	BSW	C1	F	E	72	2
40	225/40ZR18		88W	636	25.0	231	9.1	8.0	7.5- 8.5	204	8.0	8	6.5	11.1	44	560	1235	140AA A	BSW	C1	F	E	72	3
	235/40ZR18		91W	643	25.3	240	9.4	8.5	8.0- 9.0	218	8.6	8	6.5	12.2	44	615	1356	140AA A	BSW	C1	F	E	72	3
45	205/45ZR16		83W	589	23.2	209	8.2	7.0	6.5- 7.5	188	7.4	8	6.5	9.9	44	487	1073	140AA A	BSW	C1	F	E	72	3
45	215/45ZR17		87W	625	24.6	219	8.6	7.0	6.5- 7.5	196	7.7	8	6.5	10.8	44	545	1201	140AA A	BSW	C1	F	E	72	3
	225/45ZR17		94W XL	633	24.9	230	9.1	7.5	7.0- 8.0	206	8.1	7	5.2	11.2	50	670	1477	140AA A	BSW	C1	F	E	72	2
	235/45ZR17		94W	643	25.3	240	9.4	8.0	7.5- 8.5	212	8.3	8	6.5	11.6	44	670	1477	140AA A	BSW	C1	F	E	72	3
50	195/50ZR15		82W	577	22.7	200	7.9	6.0	5.5- 6.5	176	6.9	8	6.5	9.1	44	475	1047	140AA A	BSW	C1	F	E	72	3
	205/50ZR15		89W XL	589	23.2	210	8.3	6.5	6.0- 7.0	182	7.2	8	6.5	9.7	50	580	1279	140AA A	BSW	C1	F	E	72	2
50	205/50ZR16		87W	610	24.0	210	8.3	6.5	6.0- 7.0	182	7.2	8	6.5	10.0	44	545	1201	140AA A	BSW	C1	F	E	72	3