

2013/10/25

## FORMOZA AZ01

SER	SIZE	PR	LI/SS	OVERALL mm	Diameter in	Section mm	Width in	Standard Rim in	Approved Rim Width	Tread Width mm	in	Tread Depth in	32 mm	Weight KG	MAX. PSI cold	Max. Load KGS	LBS	UTQG	Side Wall	Tyres	RR	Wet Grip (dB)	E_Sound	
40	245/40ZR17		91W	632	24.9	243	9.6	8.5	8.0- 9.5	206	8.1	9	7.0	10.8	44	615	1356	380A A	BSW	C1	E	E	71	2
40	225/40ZR18		92W XL	640	25.2	226	8.9	8.0	7.5- 9.0	190	7.5	10	7.6	11.4	50	630	1389	380A A	BSW	C1	E	E	71	2
	235/40ZR18		95W XL	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	11.1	50	630	1389	380A A	BSW	C1	E	E	71	2
	245/40ZR18		93W	655	25.8	246	9.7	8.5	8.0- 9.5	205	8.1	9	7.0	12.2	44	650	1433	380A A	BSW	C1	E	E	71	2
45	195/45R16		84V XL	585	23.0	193	7.6	6.5	6.0- 7.5	156	6.1	10	7.9	7.9	50	500	1102	380A A	BSW	C1	E	E	71	2
45	215/45ZR17		91W XL	626	24.6	210	8.3	7.0	7.0- 8.0	170	6.7	10	7.6	9.7	50	615	1356	380A A	BSW	C1	E	E	71	2
	225/45ZR17		91W	635	25.0	224	8.8	7.5	7.0- 8.5	180	7.1	10	7.6	9.9	44	615	1356	380A A	BSW	C1	E	E	71	2
	235/45ZR17		97W XL	647	25.5	231	9.1	8.0	7.5- 9.0	188	7.4	10	7.6	10.2	50	730	1609	380A A	BSW	C1	E	E	71	2
	245/45ZR17		95W	653	25.7	240	9.4	8.0	7.5- 9.0	194	7.6	9	7.0	11.6	44	690	1521	380A A	BSW	C1	E	E	71	2
45	225/45ZR18		95W XL	663	26.1	220	8.7	7.5	7.0- 8.5	180	7.1	10	7.6	10.6	50	690	1521	380A A	BSW	C1	E	E	71	2
	245/45ZR18		100W XL	679	26.7	240	9.5	8.0	7.5- 9.0	194	7.6	9	7.0	11.9	44	800	1764	380A A	BSW	C1	E	E	71	2
50	205/50R16		87V	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	8.9	50	630	1389	380A A	BSW	C1	E	E	71	2
	225/50ZR16		92W	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	11.1	50	630	1389	380A A	BSW	C1	E	E	71	2
50	205/50ZR17		93W XL	637	25.1	214	8.4	6.5	5.5- 7.5	179	7.0	10	7.6	10.7	50	650	1433	380A A	BSW	C1	E	E	71	2
	215/50ZR17		95W XL	649	25.6	221	8.7	7.0	6.0- 7.5	176	6.9	10	7.6	10.3	50	690	1521	380A A	BSW	C1	E	E	71	2
	225/50ZR17		98W XL	656	25.8	236	9.3	7.0	6.0- 8.0	196	7.7	10	7.6	11.5	50	750	1653	380A A	BSW	C1	E	E	71	2
55	185/55R15		82H	587	23.1	191	7.5	6.0	5.0- 6.5	151	5.9	10	7.9	7.7	44	475	1047	380A A	BSW	C1	E	E	71	2
	195/55R15		85V	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	8.5	44	515	1135	380A A	BSW	C1	E	E	71	2
55	185/55R16		83V	611	24.0	192	7.6	6.0	5.0- 6.5	151	5.9	10	7.9	8.2	44	487	1074	380A A	BSW	C1	E	E	71	2
	195/55R16		87V	619	24.4	200	7.9	6.0	5.5- 7.0	156	6.1	10	7.9	8.6	44	545	1201	380A A	BSW	C1	E	E	71	2
	205/55ZR16		94W XL	631	24.8	209	8.2	6.5	5.5- 7.5	176	6.9	10	7.9	9.8	50	670	1477	380A A	BSW	C1	E	E	71	2
	215/55ZR16		97W XL	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	10.9	50	630	1389	380A A	BSW	C1	E	E	71	2
	225/55ZR16		99W XL	657	25.9	230	9.1	7.0	6.0- 8.0	181	7.1	10	7.6	11.0	50	775	1709	380A A	BSW	C1	E	E	71	2
55	225/55ZR17		101W XL	678	26.7	233	9.2	7.0	6.0- 8.0	192	7.6	10	7.9	11.2	50	825	1819	380A A	BSW	C1	E	E	71	2
60	185/60R15		84H	609	24.0	187	7.4	5.5	5.0- 6.5	140	5.5	10	7.9	7.5	44	500	1102	380A A	BSW	C1	E	E	71	2
	195/60R15		88H	614	24.2	198	7.8	6.0	5.5- 7.0	152	6.0	10	7.9	8.5	44	560	1233	380A A	BSW	C1	E	E	71	2
	205/60ZR15		91W	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	9.9	44	615	1355	380A A	BSW	C1	E	E	71	2
60	205/60R16		92V	650	25.6	208	8.2	6.0	5.5- 7.5	158	6.2	10	8.1	9.0	44	630	1389	380A A	BSW	C1	E	E	71	2
	215/60R16		99V XL	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	11.9	50	630	1389	380A A	BSW	C1	E	E	71	2
	225/60ZR16		98W	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	11.6	44	750	1654	380A A	BSW	C1	E	E	71	2
60	215/60R17		96H	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	11.0	44	710	1565	380A A	BSW	C1	E	E	71	2
65	175/65R15		84H	611	24.1	175	6.9	5.0	5.0- 6.0	129	5.1	10	7.9	7.5	44	500	1102	380A A	BSW	C1	E	E	71	2
	195/65R15		91V	632	24.9	203	8.0	6.0	5.0- 7.5	146	5.7	10	8.1	8.3	44	615	1356	380A A	BSW	C1	E	E	71	2
	205/65R15		95H	649	25.6	204	8.0	6.0	5.5- 7.5	152	6.0	10	8.2	9.9	44	690	1251	380A A	BSW	C1	E	E	71	2

65	215/65R16	98H	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	12.0	44	750	1653	380A A	BSW	C1	E	E	71	2
----	-----------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	----	-----	------	--------	-----	----	---	---	----	---

2013/10/25

FORMOZA AZ01 FRF

SER	SIZE	PR	LI/SS	OVERALL Diameter		Section Width		Standard Rim in	Approved Rim Width		Tread Width		Tread Depth		Weight KG	MAX. PSI			UTQG	Side Wall	Tyres	RR	Wet Grip (dBS)		E_Sound
				mm	in	mm	in		in	mm	in	in32	mm	cold		KGS	LBS								
45	225/45ZRF17		91W	638	25.1	223	8.8	7.5	7.0- 8.5	180	7.1	10	7.6	13.6	44	615	1356	380A A	FRF	C1	E	E	71	2	
50	205/50ZRF17		93W XL	640	25.2	214	8.4	6.5	5.5- 7.5	179	7.0	10	7.6	13.1	50	630	1389	380A A	FRF	N/A	N/A	N/A	N/A	N/A	
	225/50			N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	14.8	N/A	N/A	N/A	N/A	N/A	C1	E	E	71	2	
55	195/55RF16		87V	619	24.4	202	7.9	6.0	5.5- 7.0	156	6.1	10	7.9	11.9	44	545	1201	380A A	FRF	C1	E	E	71	2	
	205/55ZRF16		91W	629	24.8	214	8.4	6.5	5.5- 7.5	176	6.9	10	7.9	13.9	44	615	1356	380A A	FRF	C1	E	E	71	2	