

2013/10/11

COURAGIA A/T

| SER | SIZE | PR | LI/SS | OVERALL mm | Diameter in | Section mm | Width in | Standard Rim in | Approved Rim Width | Tread Width mm | in | Tread Depth in32 | mm | Weight KG | MAX. PSI cold | Max. Load KGS | LBS | UTQG | Side Wall |
|-----|-------------|----|----------|---------------|----------------|---------------|-------------|--------------------|--------------------|-------------------|-----|---------------------|------|--------------|------------------|------------------|-----------|--------|-----------|
| 70 | P215/70R16 | | 100T | 708 | 27.9 | 221 | 8.7 | 6.5 | 6.0- 7.0 | 174 | 6.9 | 13 | 10.1 | 14.2 | 44 | 800 | 1763 | 480A B | OWL |
| | P225/70R16 | | 101S | 721 | 28.4 | 231 | 9.1 | 6.5 | 6.0- 7.5 | 179 | 7.0 | 13 | 10.2 | 14.6 | 44 | 825 | 1819 | 480A B | OWL |
| | P235/70R16 | | 106S | 736 | 29.0 | 235 | 9.3 | 7.0 | 6.5- 7.5 | 185 | 7.3 | 13 | 10.0 | 15.6 | 44 | 950 | 2094 | 480A B | OWL |
| | P245/70R16 | | 112S XL | 748 | 29.5 | 245 | 9.6 | 7.0 | 6.5- 7.5 | 195 | 7.7 | 13 | 10.0 | 17.2 | 50 | 1120 | 2469 | 480A B | OWL |
| | P255/70R16 | | 111S | 764 | 30.1 | 260 | 10.2 | 7.5 | 7.0- 8.0 | 205 | 8.1 | 13 | 10.0 | 18.0 | 44 | 1090 | 2403 | 480A B | OWL |
| | P265/70R16 | | 112S | 778 | 30.6 | 272 | 10.7 | 8.0 | 7.5- 8.5 | 214 | 8.4 | 12 | 9.8 | 18.5 | 44 | 1120 | 2469 | 480A B | OWL |
| 70 | LT265/70R17 | 10 | 121/118Q | 803 | 31.6 | 274 | 10.8 | 8.0 | 7.5- 8.5 | 208 | 8.2 | 14 | 11.2 | 20.7 | 80 | 1450/1320 | 3197/2910 | N/A | OWL |
| | P265/70R17 | | 115S | 804 | 31.7 | 272 | 10.7 | 8.0 | 7.5- 8.5 | 214 | 8.4 | 13 | 10.2 | 20.6 | 44 | 1215 | 2679 | 480A B | OWL |
| 75 | LT215/75R15 | 6 | 100/97Q | 703 | 27.7 | 216 | 8.5 | 6.0 | 5.5- 6.5 | 158 | 6.2 | 13 | 10.3 | 14.4 | 50 | 800/ 730 | 1765/1610 | -- -- | OWL |
| | LT235/75R15 | 6 | 104/101Q | 733 | 28.9 | 235 | 9.3 | 6.5 | 6.0- 7.0 | 173 | 6.8 | 14 | 11.1 | 15.5 | 50 | 900/ 825 | 1985/1820 | -- -- | OWL |
| | P235/75R15 | | 105S | 733 | 28.9 | 235 | 9.3 | 6.5 | 6.0- 7.0 | 159 | 6.3 | 12 | 9.4 | 14.5 | 44 | 925 | 2039 | 480A B | OWL |
| 75 | LT225/75R16 | 10 | 115/112Q | 744 | 29.3 | 218 | 8.6 | 6.0 | 5.5- 6.5 | 169 | 6.7 | 15 | 11.6 | 17.5 | 80 | 1215/1120 | 2679/2469 | -- -- | BSW |
| | LT245/75R16 | 10 | 120/116Q | 774 | 30.5 | 248 | 9.8 | 7.0 | 6.5- 7.5 | 179 | 7.0 | 16 | 12.5 | 19.7 | 80 | 1380/1260 | 3042/2778 | -- -- | OWL |
| | LT265/75R16 | 10 | 123/120Q | 805 | 31.7 | 259 | 10.2 | 7.5 | 7.0- 8.0 | 203 | 8.0 | 15 | 11.8 | 21.5 | 80 | 1550/1400 | 3417/3086 | -- -- | OWL |
| | LT285/75R16 | 8 | 122/119Q | 834 | 32.8 | 286 | 11.3 | 8.0 | 7.5- 8.5 | 208 | 8.2 | 15 | 11.9 | 27.3 | 65 | 1500/1360 | 3305/3000 | -- -- | OWL |
| | P265/75R16 | | 116S | 804 | 31.7 | 267 | 10.5 | 7.5 | 7.0- 8.0 | 180 | 7.1 | 13 | 10.4 | 18.0 | 44 | 1250 | 2756 | 480A B | OWL |
| 80 | 195/80R15 | | 96S | 693 | 27.3 | 194 | 7.6 | 5.5 | 5.0- 6.5 | 147 | 5.8 | 11 | 9.0 | 11.3 | 44 | 710 | 1565 | 480A B | BSW |
| 80 | 205/80R16 | | 104S XL | 734 | 28.9 | 201 | 7.9 | 5.5 | 5.0- 6.0 | 152 | 6.0 | 11 | 8.9 | 13.8 | 50 | 900 | 1984 | 480A B | BSW |
| 85 | LT215/85R16 | 10 | 115/112Q | 774 | 30.5 | 213 | 8.4 | 6.0 | 5.5- 6.5 | 171 | 6.7 | 16 | 12.4 | 18.3 | 80 | 1215/1120 | 2679/2469 | -- -- | BSW |
| | LT235/85R16 | 10 | 120/116Q | 806 | 31.7 | 235 | 9.3 | 6.5 | 6.0- 7.0 | 170 | 6.7 | 15 | 11.9 | 20.7 | 80 | 1380/1260 | 3042/2778 | -- -- | BSW |
| 80 | 30* 9.50R15 | 6 | 104Q | 756 | 29.8 | 240 | 9.4 | 7.5 | 7.0- 8.0 | 190 | 7.5 | 16 | 12.7 | 17.2 | 50 | 900 | 1985 | -- -- | OWL |
| | 31*10.50R15 | 6 | 109Q | 781 | 30.7 | 264 | 10.4 | 8.5 | 8.0- 9.0 | 212 | 8.3 | 16 | 12.7 | 20.5 | 50 | 1030 | 227 | -- -- | OWL |