

2013/10/25

COURAGIA M/T

SER	SIZE	PR	LI/SS	OVERALL Diameter		Section Width		Standard Rim in	Approved Rim Width	Tread Width		Tread Depth		Weight KG	MAX. PSI cold	Max. Load		UTQG	Side Wall	Tyres	RR	Wet Grip (dB)		E_Sound
				mm	in	mm	in			mm	in	in	mm			in	KGS					LBS		
65	LT275/65R18	8	119/116Q	824	32.4	275	10.8	8.0	7.5- 9.0	216	8.5	20	15.6	23.5	65	1360/	2998/	N/A	BSW	N/A	N/A	N/A	N/A	N/A
70	LT265/70R17	10	121/118Q	810	31.9	272	10.7	8.0	7.0- 8.5	212	8.3	20	15.9	25.7	80	1450/1320	3195/2910	-- -	OWL	N/A	N/A	N/A	N/A	N/A
	LT285/70R17	8	121/118Q	840	33.1	287	11.3	8.5	8.0- 9.0	228	9.0	20	15.9	25.0	65	1450/1320	3195/2910	N/A	OWL	N/A	N/A	N/A	N/A	N/A
75	LT235/75R15	6	104/101Q	734	28.9	228	9.0	6.5	6.0- 7.0	168	6.6	19	15.0	16.6	50	900/ 825	1985/1820	-- -	OWL	N/A	N/A	N/A	N/A	N/A
75	LT265/75R16	8	119/116Q	807	31.8	260	10.2	7.5	7.0- 8.0	193	7.6	19	15.0	23.0	65	1360/1250	3000/2755	-- -	OWL	N/A	N/A	N/A	N/A	N/A
	LT285/75R16	8	122/119Q	835	32.9	281	11.1	8.0	7.5- 9.0	208	8.2	19	15.0	25.3	65	1500/1360	3305/3000	-- -	OWL	N/A	N/A	N/A	N/A	N/A
80	LT205/80R16	8	110/108Q	734	28.9	210	8.3	5.5	5.0- 7.0	160	6.3	19	15.0	17.0	65	1060/1000	2337/2205	-- -	OWL	N/A	N/A	N/A	N/A	N/A
85	LT235/85R16	10	120/116Q	806	31.7	231	9.1	6.5	6.0- 7.5	170	6.7	19	15.0	21.1	80	1400/1260	3086/2778	-- -	OBL	N/A	N/A	N/A	N/A	N/A
80	30* 9.50R15	6	104Q	757	29.8	252	9.9	7.5	6.5- 8.5	192	7.6	19	15.0	19.6	35	900	1985	-- -	OWL	N/A	N/A	N/A	N/A	N/A
	31*10.50R15	6	109Q	785	30.9	268	10.6	8.5	7.0- 9.0	200	7.9	19	15.0	21.0	50	1030	2270	-- -	OWL	N/A	N/A	N/A	N/A	N/A
	33*12.50R15	6	108Q	833	32.8	325	12.8	10.0	8.5-11.0	248	9.8	19	15.0	27.4	35	1000	2205	-- -	OWL	N/A	N/A	N/A	N/A	N/A
	35*12.50R15	6	113Q	883	34.8	343	13.5	10.0	9.5-10.5	252	9.9	21	16.7	28.9	35	1150	2535	N/A	BSW	N/A	N/A	N/A	N/A	N/A
80	35*12.50R17	10	125Q	884	34.8	313	12.3	10.0	9.5-10.5	248	9.8	21	16.7	32.9	65	1650	3637	-- -	OWL	N/A	N/A	N/A	N/A	N/A
80	35*12.50R18	10	123Q	886	34.9	309	12.2	10.0	9.5-10.5	248	9.8	21	16.7	31.7	65	1550	3415	-- -	BSW	N/A	N/A	N/A	N/A	N/A
80	33*12.50R20	10	114Q	833	32.8	313	12.3	10.0	9.5-10.5	256	10.1	21	16.7	28.0	65	1180	2600	-- -	BSW	N/A	N/A	N/A	N/A	N/A
	35*12.50R20	10	121Q	883	34.8	318	12.5	10.0	8.5-11.0	256	10.1	21	16.3	31.6	65	1450	3195	-- -	BSW	N/A	N/A	N/A	N/A	N/A