

2013/10/25

COURAGIA S/U

SER	SIZE	PR	LI/SS	OVERALL Diameter		Section Width		Standard Rim in	Approved Rim Width	Tread Width		Tread Depth		Weight KG	MAX. PSI cold	Max. Load		UTQG	Side Wall	Tyres	RR	Wet Grip (dB)		E_Sound
				mm	in	mm	in			mm	in	in32	mm			KGS	LBS					C	C	
30	255/30ZR22		95Y XL	713	28.1	255	10.0	9.0	8.5- 9.5	249	9.8	11	8.9	15.2	50	690	1522	420A A	BSW	C1	F	C	75	3
	265/30R22		93V	719	28.3	265	10.4	9.5	9.0-10.0	252	9.9	11	8.5	16.2	44	650	1433	420A A	BSW	C1	F	C	75	3
35	285/35ZR22		106W XL	759	29.9	290	11.4	10.0	9.5-11.0	265	10.4	11	8.9	19.1	50	950	2094	420A A	BSW	C1	F	C	75	2
35	305/35R24		112V XL	824	32.4	305	12.0	11.0	10.0-12.0	290	11.4	11	8.6	21.2	50	1120	2469	420A A	BSW	C1	F	C	75	2
40	295/40R20		106V	749	29.5	300	11.8	10.5	10.0-11.5	251	9.9	11	8.6	19.3	44	950	2094	420A A	BSW	C1	F	C	75	3
40	295/40R24		114V XL	851	33.5	307	12.1	10.5	10.0-11.5	251	9.9	11	8.6	22.4	50	1180	2601	420A A	BSW	C1	F	C	75	2
45	255/45R20		105V XL	739	29.1	252	9.9	8.5	8.0- 9.5	216	8.5	11	8.9	15.5	50	925	2039	420A A	BSW	C1	F	C	75	3
	295/45R20		114V XL	774	30.5	296	11.7	10.0	9.5-11.0	259	10.2	10	8.2	19.4	50	1180	2601	420A A	BSW	C1	F	C	75	2
45	305/45R22		118V XL	832	32.8	299	11.8	10.0	9.5-11.5	259	10.2	11	8.6	22.0	50	1320	2911	420A A	BSW	C1	F	C	75	2
50	285/50R20		112V	N/A	N/A	N/A	N/A	N/A	N/A N/A	N/A	N/A	N/A	N/A	20.4	44	950	2094	320A A	BSW	C1	F	C	75	3
	305/50R20		120V XL	815	32.1	311	12.2	9.5	8.5-10.5	268	10.6	11	8.6	23.0	50	1400	3086	420A A	BSW	C1	F	C	75	2
55	275/55R17		109V	733	28.9	289	11.4	8.5	8.0- 9.0	257	10.1	11	8.9	17.5	44	1030	2271	420A A	BSW	C1	F	C	75	3
55	275/55R20		117V XL	812	32.0	286	11.3	8.5	7.5- 9.5	257	10.1	12	9.4	20.3	50	1285	2833	420A A	BSW	C1	F	C	75	3
60	255/60R15		102H	687	27.0	251	9.9	7.5	7.0- 9.0	204	8.0	11	8.9	13.8	44	850	1874	420A A	BSW	C1	F	C	75	3
	275/60R15		107H	710	28.0	269	10.6	8.0	7.5- 9.5	219	8.6	11	8.9	15.4	44	975	2150	420A A	BSW	C1	F	C	75	3
60	275/60R16		109H	736	29.0	270	10.6	8.0	7.5- 9.5	219	8.6	11	8.6	16.3	44	1030	2271	420A A	BSW	C1	F	C	75	3
60	225/60R17		105H XL	703	27.7	226	8.9	6.5	6.0- 7.0	182	7.2	10	7.9	12.7	50	925	2039	420A A	BSW	C1	F	C	75	3
	275/60R17		111V	765	30.1	270	10.6	8.0	7.5- 9.5	220	8.7	10	8.3	18.1	44	1090	2403	420A A	BSW	C1	F	C	75	3
60	285/60R18		116V	800	31.5	283	11.2	8.5	8.0-10.0	228	9.0	11	8.4	19.4	44	1250	2756	420A A	BSW	C1	F	C	75	3
60	275/60R20		119V XL	839	33.0	275	10.8	8.0	7.5- 9.5	220	8.7	11	8.7	20.7	50	1360	2998	420A A	BSW	C1	F	C	75	3
65	225/65R18		103H	750	29.5	225	8.9	6.5	6.0- 8.0	176	6.9	12	9.2	15.0	44	875	1929	420A A	BSW	C1	F	C	75	3
70	225/70R15		100H	696	27.4	220	8.7	6.5	6.0- 7.5	182	7.2	12	9.4	13.3	44	800	1764	420A A	BSW	C1	F	C	75	3
	255/70R15		112H XL	740	29.1	249	9.8	7.5	6.5- 8.5	206	8.1	12	9.8	17.3	50	1120	2469	420A A	BSW	C1	F	C	75	3
	265/70R15		112H	755	29.7	260	10.2	8.0	7.0- 9.0	214	8.4	13	10.3	18.3	44	1120	2469	420A A	BSW	C1	F	C	75	3
70	235/70R16		106H	736	29.0	237	9.3	7.0	6.0- 8.0	190	7.5	12	9.6	16.3	44	950	2094	420A A	BSW	C1	F	C	75	3
	245/70R16		107H	750	29.5	238	9.4	7.0	6.5- 8.0	198	7.8	12	9.8	17.3	44	975	2149	420A A	BSW	C1	F	C	75	3
	255/70R16		111H	764	30.1	247	9.7	7.5	6.5- 8.5	206	8.1	12	9.9	18.3	44	1090	2403	420A A	BSW	C1	F	C	75	3