

2013/10/16

COURAGIA XUV

SER	SIZE	PR	LI/SS	OVERALL Diameter		Section Width		Standard Rim	Approved Rim Width		Tread Width		Tread Depth		Weight	MAX. PSI	Max. Load		UTQG	Side Wall	Tyres	RR	Wet Grip (dB)		E_Sound
				mm	in	mm	in	in	in	in	mm	in	in	mm	KG	col	KGS	LBS							
55	P235/55R17		99H	689	27.1	242	9.5	7.5	6.5- 8.5	200	7.9	10	8.0	12.3	44	775	1709	440A A	BSW	C1	E	E	74	3	
55	P225/55R18		98V	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	13.0	44	750	653	440A A	BSW	N/A	N/A	N/A	N/A	N/A	
	P235/55R18		104V XL	715	28.2	244	9.6	7.5	6.5- 8.5	201	7.9	10	8.3	13.5	49	900	1984	440A A	BSW	C1	E	E	74	3	
60	P235/60R16		100H	687	27.1	236	9.3	7.0	6.5- 8.5	187	7.4	11	8.4	12.6	440	800	1764	440A A	BSW	C1	E	E	74	3	
60	P225/60R17		99H	703	27.7	224	8.8	6.5	6.0- 8.0	178	7.0	10	8.2	12.4	44	775	1708	440A A	BSW	C1	E	E	74	3	
	P235/60R17		102V	713	28.1	240	9.4	7.0	6.5- 8.5	187	7.4	11	8.4	13.6	44	850	1874	440A A	BSW	C1	E	E	74	3	
	P255/60R17		110V XL	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	15.5	50	1060	2337	440A A	BSW	C1	E	E	74	3	
60	P245/60R18		105H	752	29.6	244	9.6	7.0	7.0- 8.5	194	7.6	11	8.4	14.5	44	850	1874	440A A	BSW	N/A	N/A	N/A	N/A	N/A	
	P265/60R18		110H	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	16.2	44	1060	2337	440A A	BSW	C1	E	E	74	3	
65	P215/65R16		98H	688	27.1	222	8.7	6.5	6.0- 7.0	168	6.6	10	8.3	11.9	44	750	1653	440A A	BSW	C1	E	E	74	3	
	P255/65			N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	15.1	N/A	N/A	N/A	N/A	N/A	C1	E	E	74	3	
65	P225/65R17		102H	722	28.4	229	9.0	6.5	6.0- 8.0	174	6.9	10	8.3	13.4	44	850	1874	440A A	BSW	C1	E	E	74	3	
	P235/65R17		108V XL	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	13.7	50	1000	2205	440A A	BSW	C1	E	E	74	3	
	P245/65R17		111H XL	748	29.5	253	10.0	7.0	7.0- 8.0	189	7.4	11	8.6	14.7	50	1090	2403	440A A	BSW	C1	E	E	74	3	
	P265/65R17		112H	725	28.6	230	9.0	6.5	6.0- 7.5	166	6.5	11	8.6	18.8	44	875	1929	440A A	BSW	N/A	N/A	N/A	N/A	N/A	
65	P235/65R18		106H	766	30.1	236	9.3	7.0	6.5- 8.5	168	6.6	11	8.6	14.1	44	950	2094	440A A	BSW	C1	E	E	74	3	
70	P205/70R15		96H	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	10.7	44	710	1565	440A A	BSW	C1	E	E	74	3	
	P255/70R15		112H XL	742	29.2	254	10.0	7.5	6.5- 8.5	189	7.4	11	8.8	14.6	50	1120	2469	440A A	BSW	C1	E	E	74	3	
	P265/70R15		112H	755	29.7	264	10.4	8.0	7.0- 9.0	198	7.8	11	8.8	16.0	44	1120	2469	440A A	BSW	C1	E	E	74	3	
70	P215/70R16		100H	708	27.9	225	8.8	6.5	5.5- 7.0	86	3.4	11	8.9	12.4	440	800	1764	440A A	BSW	C1	E	E	74	3	
	P225/70R16		103H	725	28.6	230	9.0	6.5	6.0- 7.5	166	6.5	11	8.6	12.8	44	875	1929	440A A	BSW	C1	E	E	74	3	
	P235/70R16		106H	736	29.0	232	9.1	7.0	6.0- 8.0	174	6.9	11	8.7	14.3	44	950	2094	440A A	BSW	C1	E	E	74	3	
	P245/70R16		107H	752	29.6	247	9.7	7.0	6.5- 8.0	243	9.6	11	8.7	14.5	44	975	2150	440A A	BSW	N/A	N/A	N/A	N/A	N/A	
	P255/70R16		111H	766	30.1	256	10.1	7.5	6.5- 8.5	189	7.4	11	8.8	15.6	44	1090	2403	440A A	BSW	C1	E	E	74	3	
	P265/70R16		112H	777	30.6	273	10.8	8.0	7.0- 9.0	99	3.9	11	8.8	16.1	44	1120	2469	440A A	BSW	C1	E	E	74	3	
	P275/70R16		114H	793	31.2	272	10.7	8.0	7.0- 9.0	102	4.0	11	8.5	17.5	44	1180	2601	440A A	BSW	C1	E	E	74	3	
70	LT265/70R17	10	121/118S	773	30.4	248	9.8	7.0	N/A	N/A	188	7.4	14	11.0	21.0	80	/1120	/2469	N/A	BSW	N/A	N/A	N/A	N/A	N/A
	P265/70R17		115H	725	28.6	230	9.0	6.5	6.0- 7.5	166	6.5	11	8.6	20.6	44	875	1929	440A A	BSW	N/A	N/A	N/A	N/A	N/A	
75	LT225/75R16	10	115/112S	773	30.4	248	9.8	7.0	N/A	N/A	188	7.4	14	11.0	12.6	80	/1120	/2469	N/A	BSW	N/A	N/A	N/A	N/A	N/A
	LT245/75R16	10	120/116S	773	30.4	248	9.8	7.0	N/A	N/A	188	7.4	14	11.0	19.0	80	/1260	/2778	N/A	BSW	N/A	N/A	N/A	N/A	N/A
	LT265/75R16	10	112/109S	773	30.4	248	9.8	7.0	N/A	N/A	188	7.4	14	11.0	28.7	80	/1120	/2469	N/A	BSW	N/A	N/A	N/A	N/A	N/A