

ER01

SER	SIZE	PR	LI/SS	OVERALL mm	Diamete r in	Sectio n mm	Width	Standard Rim in	Approve d Rim Width	Tread mm	Width in	Tread in32"	Depch mm	Weigh t KG	MAX. PS I cold	Max. KG	Load LBS	UTQG	Side Wall	Tires	RR	wet Grip	dBS	E-Sound
60	215/60R16C	8	108/106R	664.7	26.2	217.4	8.6	6.5	6.0-7.0	172.6	6.8	13.5	10.7	13.4	69	1000/950	2205/2094		C2	G	C	75	3	
	175/65R14C	6	90/88T	583	22.9	168	6.6	5	4.5-5.5	130	5.1	12.1	9.6	8.7	54	600/560	1323/1235		C2	G	C	75	3	
	205/65R16C	8	107/105T	671	26.4	204	8	6	5.5-6.5	204	8	14	11.1	12.8	69	975/925	2150/2039		C2	G	C	75	3	
65	215/65R16C	8	109/107T	685.7	27	211.8	8.3	6.5	6.0-7.0	165	6.5	13.6	10.8	13.7	69	1030/975	2271/2150		C2	G	C	75	3	
	225/65R16C	8	112/110R	697	27.4	223	8.8	6.5	6.0-7.0	170	6.7	13.9	11.1	14.4	69	1120/1060	2469/2336		C2	G	C	75	3	
	235/65R16C	8	115/113R	712.7	28.1	236	9.3	7	6.5-7.5	180	7.1	13.5	10.7	14.5	69	1215/1150	2678/2535		C2	G	C	75	3	
	165/70R14C	8	89/87R	589.8	23.2	165.8	6.5	5	4.5-5.5	123.7	4.9	10.2	8.1	8.8	55	580/545	1279/1202		C2	G	C	75	3	
	195/70R15C	8	104/102R	656.1	25.8	199.1	7.8	6	5.5-6.5	146	5.7	11.5	9.1	12.5	65	900/850	1981/1874		C2	G	C	75	3	
	205/70R15C	8	106/104S	669	26.3	210	8.3	6.5	6.0-7.0	210	8.3	12.3	9.8	13.1	54	950/900	2094/1984		C2	G	C	75	3	
70	#215/70R15C	6	106/104R	683.7	26.9	216.8	8.5	6.5	6.0-7.0	162	6.4	10	8	12.9	54	950/900	2094/1984		C2	G	C	75	3	
	215/70R15C	8	109/107R	684.1	26.9	223	8.8	6.5	6.0-7.0	162	6.4	12.3	9.8	13.6	65	1030/975	2270/2149		C2	G	C	75	3	
	225/70R15C	8	112/110R	697	27.4	230	9.1	6.5	6.0-7.0	230	9.1	13.1	10.4	15	54	1120/1060	2469/2336		C2	G	C	75	3	
	205/75R14C	8	109/107Q	663.4	26.1	197.5	7.8	5.5	5.0-6.0	144	5.7	13	10.3	12.5	69	1030/975	2271/2150		C2	G	C	75	3	
	215/75E14C	8	112/110Q	679.3	26.7	209.6	8.3	6	5.5-6.5	154	6.1	13	10.7	13.6	69	1120/1060	2469/2336		C2	G	C	75	3	
	175/75R16C	8	101/99R	669.1	26.3	170.1	6.7	5	4.5-5.5	125	4.9	13.7	10.9	11.1	69	825/775	1819/1709		C2	G	C	75	3	
	185/75R16C	8	104/102R	684.1	26.9	178.6	7	5	4.5-5.5	130	5.1	12.9	10.3	12	69	900/850	1984/1874		C2	G	C	75	3	
75	195/75R16C	10	110/108R	698.1	29.5	189.6	7.5	5.5	5.0-6.0	129	2.5	13.5	10.7	12.5	76	1060/1000	2337/2205		C2	G	C	75	3	
	205/75R16C	8	110/108R	714.7	28.1	208.2	8.2	6.5	6.0-7.0	144	5.7	13.7	10.9	14.2	69	1060/1000	2337/2205		C2	G	C	75	3	
	215/75R16C	8	116/114R	727.7	28.9	214.2	8.4	6	5.5-6.5	154	6.1	13.5	10.8	15.4	76	1520/1180	2756/2601		C2	G	C	75	3	
	225/75R16C	10	121/120R	745.5	29.4	216.3	8.5	6	5.5-6.5	215	8.5	13.2	10.5	17.1	83	1450/1400	3197/3086		C2	G	C	75	3	
	145R12C	8	86/84P	539.5	21.2	149.3	5.9	4	3.5-4.0	109	4.3	10.9	8.7	7	65	530/500	1168/1102		C2	G	C	75	3	
	155R12C	8	88/86P	552.6	21.8	161.8	6.4	4.5	4.0-4.5	116	4.6	11.2	8.9	7.8	65	560/530	1235/1168		C2	G	C	75	3	
	155R13C	8	90/88P	581.8	22.9	159.9	6.3	4.5	4.5-5.0	160	6.3	9.7	7.7	8.2	65	600/560	1323/1235		C2	G	C	75	3	
	165R13C	8	94/92Q	601.3	23.7	172	6.8	4.5	4.0-5.0	124	4.9	10	7.9	9.2	65	670/630	1477/1289		C2	G	C	75	3	
	175R13C	8	97/95Q	608.6	24	175.3	6.9	5	4.5-5.5	130	5.1	11.8	9.4	10	65	730/690	1610/1521		C2	G	C	75	3	
	185R13C	8	100/98Q	626.8	24.7	194.5	7.7	5.5	5.0-6.0	138	5.4	12.6	10	10.5	65	800/750	1764/1654		C2	G	C	75	3	
	165R14C	8	97/95Q	624.8	24.6	171	6.7	4.5	4.0-5.0	124	4.9	12	9.6	9.6	65	730/690	1609/1521		C2	G	C	75	3	
	175R14C	8	99/98Q	635.9	25	135.2	5.3	5	4.5-5.5	121	4.8	11.5	9.2	10.4	65	775/750	'09/1654		C2	G	C	75	3	
	185R14C	8	102/100R	649.7	25.6	192.5	7.6	5.5	5.0-6.0	138	5.4	12.3	9.8	11.4	65	850/800	1873/1763		C2	G	C	75	3	
	195R14C	8	106/104R	666	26.2	200	7.9	5.5	5.0-6.0	200	7.9	13.2	10.5	12.9	65	950/900	2094/1984		C2	G	C	75	3	
	205R14C	8	109/107P	681.5	26.8	209.8	8.3	6	5.5-6.5	154	6.1	12.8	13.8	13.8	65	1030/975	2270/2149		C2	G	C	75	3	
	215R14C	8	112/110Q	700.9	27.6	221.3	8.7	6	5.5-7.0	163	6.4	12.8	10.2	14.7	65	1120/1060	2469/2336		C2	G	C	75	3	
	185R15C	8	103/102R	675.6	26.6	194.2	7.6	5.5	5.0-6.0	138	5.4	14.1	11.2	12.4	65	875/850	1929/1874		C2	G	C	75	3	
	195R15C	8	106/104R	690.3	27.2	201.8	7.9	5.5	5.0-6.0	146	5.7	13.6	10.8	13.9	65	950/900	2094/1984		C2	G	C	75	3	
	*LT5.00R12	8	83/81P	567.8	22.4	144	5.7	3.5	3.0-4.0	105	4.1	10.8	8.6	7.5	65	487/462	1074/1019		C2	G	C	75	3	