

SER	SIZE	PR	LI/SS	OVERALL Diameter		Section Width		Standard Rim in	Approved Rim Width		Tread Width		Tread Depth		Weight KG	MAX. PSI		Max. Load KGS LBS	UTQG	Side Wall	Tyres	RR	Wet Grip (dBS)	E_Sound
				mm	in	mm	in		in	mm	in	in32	mm	cold		KGS	LBS							
60	165/60R14		75H	553	21.8	173	6.8	5.0	4.5- 5.5	132	5.2	9.8	7.8	6.2	36	387	853	420A A	BSW C1	F	C	70	2	
60	175/60R14		79H	567	22.3	175	6.9	5.0	5.5- 5.5	140	5.5	9.2	7.3	6.9	36	437	964	420A A	BSW C1	F	C	70	2	
60	185/60R13		80H	554	21.8	192	7.5	5.5	5.0-6.0	152	6.0	10	7.9	7.1	36	450	992	420A A	BSW C1	F	C	70	2	
60	185/60R14		82H	579	22.8	188	7.4	5.5	5.0- 6.0	148	5.8	9.8	7.8	7.7	36	475	1047	420A A	BSW C1	F	C	70	2	
60	185/60R15		84H	602	23.7	194	7.6	5.5	5.0- 6.0	148	5.8	10.5	8.0	8.3	36	500	1102	420A A	BSW C1	F	C	70	2	
	195/60R14		86H	589	23.2	202	8.0	6.0	5.5- 6.5	156	6.1	10	7.9	8.3	36	530	1168	420A A	BSW C1	F	C	70	2	
60	185/60R15		84H	607	23.9	184	7.2	5.5	5.0- 6.0	148	5.8	10	8.0	8.1	36	500	1102	420A A	BSW C1	F	C	70	2	
	195/60R15		88H	617	24.3	195	7.7	6.0	5.5- 6.5	156	6.1	10	7.9	8.6	36	560	1234	420A A	BSW C1	F	C	70	2	
	205/60R15		91H	626	24.6	220	8.7	6.0	5.5- 6.5	168	6.6	11	8.7	9.9	36	615	1355	420A A	BSW C1	F	C	70	2	
60	205/60R13		87H	576	22.7	210	8.3	6.0	5.5- 5.5	168	6.6	10.2	8.1	9.0	36	545	1201	420A A	BSW C1	F	C	70	2	
	215/60R16		95H	663	26.1	225	8.9	6.5	6.0- 7.0	172	6.8	11	9.0	11.0	36	690	1521	420A A	BSW C1	F	C	70	2	
	225/60R16		98H	675	26.6	228	9.0	6.5	6.0- 7.0	184	7.2	11	8.7	12.2	36	750	1653	420A A	BSW C1	F	C	70	2	
	155/65R13		73T	532	20.9	158	6.2	4.5	4.5- 5.5	121	4.8	10	7.7	5.5	36	365	805	420A A	BSW C1	F	C	70	2	
	165/65R13		77H	545	21.4	171	6.7	5.0	4.0- 5.0	128	5.1	10	8.1	6.4	36	412	908	420A A	BSW C1	F	C	70	2	
	175/65R14		82H	584	23.0	176	7.0	5.0	5.5- 5.5	137	5.4	9.7	7.7	7.2	36	475	1047	420A A	BSW C1	F	C	70	2	
	175/65R14		86T XL	584	23.0	176	7.0	5.0	5.5-5.5	137	5.4	9.1	7.2	7.7	51	530	1168	420A A	BSW C1	F	C	70	2	
	185/65R14		86H	595	23.4	193	7.6	5.5	5.0- 6.0	144	5.7	10	8.2	7.8	36	530	1168	420A A	BSW C1	F	C	70	2	
65	185/65R15		88H	622	24.5	188	7.4	5.5	5.0- 6.0	144	5.7	10	8.4	8.3	36	560	1235	420A A	BSW C1	F	C	70	2	
	195/65R15		91H	634	25.0	202	8.0	6.0	5.5- 6.5	152	6.0	10	8.2	9.1	36	615	1355	420A A	BSW C1	F	C	70	2	
	195/65R15		95T XL	637	25.1	200	7.9	6.0	5.5- 6.5	152	6.0	9.1	7.2	8.7	36	690	1521	420A A	BSW C1	F	C	70	2	
	205/65R15		95H	647	25.5	208	8.2	6.0	5.5-6.5	160	6.3	10	7.9	10.3	36	710	1565	420A A	BSW C1	F	C	70	2	
	215/65R15		96H	662	26.0	222	8.7	6.5	6.0- 7.5	167	6.6	9.2	7.3	11.0	36	710	1565	420A A	BSW C1	F	C	70	2	
	145/70R12		69T	512	20.2	148	5.8	4.5	4.0- 5.0	105	4.1	8.8	7.0	5.2	44	325	717	420A A	BSW C1	F	C	70	2	
	145/70R13		71T	535	21.1	152	6.0	4.5	4.0- 5.0	105	4.1	9.3	7.4	5.5	36	345	761	420A A	BSW C1	F	C	70	2	
	155/70R13		75T	546	21.5	160	6.3	4.5	4.0- 5.0	113	4.4	9.8	7.8	6.1	36	387	853	420A A	BSW C1	F	C	70	2	
	165/70R13		79T	560	22.0	170	6.7	5.0	4.5- 5.5	120	4.7	10.0	7.9	6.6	36	437	963	420A A	BSW C1	F	C	70	2	
	175/70R13		82T	580	22.8	179	7.0	5.0	4.5- 5.5	127	5.0	10.1	8.0	7.2	36	475	1047	420A A	BSW C1	F	C	70	2	
	185/70R13		86T	589	23.2	192	7.6	5.5	5.0- 6.0	134	5.3	10.0	8.0	7.4	36	530	1168	420A A	BSW C1	F	C	70	2	
70	165/70R14		81T	589	23.2	171	6.7	5.0	4.5- 5.5	120	4.7	10.0	8.0	6.7	36	462	1018	420A A	BSW C1	F	C	70	2	
	165/70R14		85TXL	587	23.1	171	6.7	5.0	4.5- 5.5	120	4.7	9.2	7.3	6.9	50	515	1135	420A A	BSW C1	F	C	70	2	
	175/70R14		84T	602	23.7	180	7.1	5.0	4.5- 5.5	127	5.0	10.2	8.1	7.5	36	500	1102	420A A	BSW C1	F	C	70	2	
	185/70R14		88T	619	24.4	194	7.6	5.5	5.0-6.0	132	5.2	10.3	8.2	8.3	36	560	1234	420A A	BSW C1	F	C	70	2	
	195/70R14		91T	629	24.8	202	8.0	6.0	5.5- 6.5	138	5.4	10.6	8.4	9.4	36	615	1355	420A A	BSW C1	F	C	70	2	
	205/70R14		95T	645	25.4	211	8.3	6.0	5.5- 6.5	149	5.9	9.1	7.2	10.1	36	690	1521	420A A	BSW C1	F	C	70	2	
	205/70R15		96T	667	26.3	211	8.3	6.0	5.5- 6.5	149	5.9	10.2	8.1	10.8	36	710	1565	420A A	BSW C1	F	C	70	2	
	205/70R15		98T	681	27.0	226	8.9	6.5	6.0-7.0	156	6.1	10.2	8.1	11.7	36	750	1653	420A A	BSW C1	F	C	70	2	
	155/80R12		77T	553	21.8	159	6.3	4.5	4.0- 5.0	107	4.2	9.4	7.5	6.0	35	412	908	420A A	BSW C1	F	C	70	2	
	135/80R13		70T	546	21.5	138	5.4	3.5	4.0- 4.5	93.2	3.7	9.2	7.3	5.3	35	335	739	420A A	BSW C1	F	C	70	2	
	145/80R13		75T	562	22.1	149	5.9	4.0	3.5- 4.5	101	4.0	9.3	7.4	5.8	35	387	853	420A A	BSW C1	F	C	70	2	
80	155/80R13		79T	578	22.8	159	6.3	4.5	4.0- 4.5	107	4.2	9.4	7.5	6.6	35	437	963	420A A	BSW C1	F	C	70	2	

165/80R13	83T	594	23.4	167	6.6	4.5	4.0- 5.0	114	4.5	9.6	7.6	7.3	35	487	1073	420A A	BSW	C1	F	C	70	2
175/80R14	88T	636	25.0	179	7.1	5.0	4.5- 5.5	121	4.8	9.7	7.7	8.0	36	560	1234	420A A	BSW	C1	F	C	70	2
185/80R14	91T	650	25.6	189	7.4	5.0	4.5- 5.5	128	5.0	10.0	7.9	9.3	36	615	1355	420A A	BSW	C1	F	C	70	2
165/80R15	87T	644	25.4	171	6.7	5.0	4.5- 5.5	128	5.0	10.0	7.9	8.2	35	615	1355	420A A	BSW	C1	F	C	70	2
185/80R15	93T	677	26.7	150	5.9	5.0	4.5- 5.5	128	5.0	9.6	7.6	10.0	35	650	1433	420A A	BSW	C1	F	C	70	2

---